

# BARISTA 600 TOUCH

## INSTALLATION SITE PREPARATION CHECKLIST



Necta

### GENERAL MACHINE ENVIRONMENT


- The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- The machine is installed in a dry room, far from any source of heat (temperature between 41°F and 93°F).
- The installation area accommodates the machine size and weight:
  - Dimensions: 23.6" (W) x 74.0" (H) x 29.1" (D)
  - Dry Weight: 297.62 lb
- The inclination does not exceed 2 degrees (machine leveled using the adjustable feet, if necessary).
- Machine can safely be installed with minimum clearance:
  - Front: 20" – Opening the door.
  - Right Side: 23.6" – Complete opening of the door.
  - Back: 1.6" – Providing regular ventilation.

### ELECTRICAL REQUIREMENTS

<b>Barista 600 Touch Specifications</b>	110-120 V / 60 Hz, 1250 W NEMA 5-15P
-----------------------------------------	-----------------------------------------

- Power outlet receptacle is NEMA 5-15R.
- Dedicated electrical circuit meets the Barista 600 Touch power requirements.
- No extension cord or power strip on the circuit.

#### NEMA 5-15



#### Legend



### WATER REQUIREMENTS

#### Pressure & Hardness

- Pressure is between 7.3 psig and 123.3 psig (0.5 and 8.5 bar).
- pH range is between 6.5 and 7.5.
- Hardness (TDH) is between 89 PPM and 142 PPM.

**MANDATORY** – Machine water line must be equipped with a water filtration system with softness/filtration capabilities and a descaling device.

#### Water Network

- The water network provides cold, drinkable tap water.
- Dedicated 1/4" or 3/8" diameter water line.
- Easily accessible dedicated shutoff valve on machine's end.

