



MAXIMUM TIME BETWEEN EACH MAINTENANCE 4 MONTHS															
	YEAR 1			YEAR 2			YEAR 3			YEAR 4			YEAR 5		
CYCLES	10 000	20 000	30 000	40 000	50 000	60 000	70 000	80 000	90 000	100 000	110 000	120 000	130 000	140 000	150 000
MAINTENANCE TYPE	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	Overall control	At the end of the fifth year GENERAL REVISION
MAINTENANCE TYPE	A	A	A	A	A	A	A	A	A	A	A	A	A	A	
MAINTENANCE TYPE						B						B			
MAINTENANCE TYPE									C						
			D			D			D			D			
MAINTENANCE TYPE									E			F			

A	Replacement of the components listed in table A.
----------	--

B	Replacement of the components listed in table B.
----------	--

C	Replacement of the components listed in table C.
----------	--

D	Replacement of the components listed in table D.
----------	--

E	Replacement of the components listed in table E or F.
----------	---

Overall control	Report the data referring to the number of Cycles. Control of all the functions of the most important components of the machine: pumps, grinder, safety valve, expansion valves, volumetric meters, level probe, pressure sensor (pressure switch), correct sealing of the internal and external pipes of the machine, electrical connections. Control of the components through the Test Program to be carried out on the machine verifiable on the display. Brew unit: cleaning of the unit and control of the filters, alignment of the piston with the plane of the body of the unit, centering of the upper counter-plate with the coffee container, checking of the connecting rod and camshaft, lubrication of the guide shafts. Control settings: Make sure that all the parameters set for each selection are always correct, check the degree of grinding and the weight of the coffee powder for each single or double dose of both grinders, check the data set for each display function . Water hardness check and correct softener operation.
------------------------	--

Concetto EVO DUO

Maintenance Type & Parts Kits



Overall control				
Description of the Service to Be Performed				TIME
See Previous Chart				50 mins
MAINTENANCE TYPE A				
Description of the Service to Be Performed	QTY	PART NUMBER	CODE	TIME
Cleaning Coffee Circuit				30 mins
Cleaning Milk Circuit				
Drainage Cleaning Behind the Brew Unit				
Gray Drainage Channel Cleaning				
Coffee Channel Cleaning				
Hot Water Dispenser Cleaning				
Replace Coffee Brewer Filters	1		20PMK02-A	
MAINTENANCE TYPE B				
Description of the Service to Be Performed	QTY	PART NUMBER	CODE	TIME
Replace Vacuum Valve	1	9040,008	20PMK02-B	20 min
MAINTENANCE TYPE C				
Description of the Service to Be Performed	QTY	PART NUMBER	CODE	TIME
Replace PressureSwitch	1	NE08.004	20PMK02-C	10 min
Replace Steam Tap Assembly	1	263371		10 min
Replace Water Tap Assembly	1	9180.015		10 min
Replace Pump Replacement	4	11032096		30 min
Replace Coffee Boiler Assembly	1	263394		30 min
MAINTENANCE TYPE D				
Description of the Service to Be Performed	QTY	PART NUMBER	CODE	TIME
Replace Brew Unit	1	11010042	20PMK02-D	5 min
Replace Cappuccinatore	1	1037.035.050		5 min
MAINTENANCE TYPE E				
Description of the Service to Be Performed	QTY	PART NUMBER	CODE	TIME
Repape Blades of Both Grinders	4	263369	20PMK02-E	40 min
MAINTENANCE TYPE F				
Description of the Service to Be Performed	QTY	PART NUMBER	CODE	TIME
Replace Ratio Motor	1	11002139	20PMK02-F	30 min