



EMBLEM

INSTALLATION SITE PREPARATION CHECKLIST



GENERAL MACHINE ENVIRONMENT

- The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- The counter accommodates the machine size and weight:
 - Dimensions: 22.0" (W) x 29.3" (H) x 23.9" (D)
 - Dry Weight: 98 lb
- For under counter waste bin installation, a hole has been cut in the counter in accordance with model chute kit template.
- Machine can safely be installed with minimum clearance:
 - Top: 6" – Necessary for filling the machine from the top, but it can also be refilled from the front.
 - Sides: 6" – Opening the door and accessing the lock.
 - Back: 1.75" – Electrical and water connections space.


ELECTRICAL REQUIREMENTS

Emblem Specifications	120 V / 60 Hz, 1440 W NEMA 5-15P GFCI Plug
------------------------------	---

- Power outlet receptacle is NEMA 5-15R.
- Dedicated electrical circuit meets the Emblem power requirements.
- No extension cord or power strip on the circuit.



NEMA 5-15



WATER REQUIREMENTS

Pressure & Hardness

- Pressure is between 20 PSI and 80 PSI.
- pH range is between 6 and 8.
- General hardness is between 10 and 70 mg/L.

MANDATORY – Machine water line must be equipped with a water filtration system with softness/filtration capabilities and a descaling device.

Water Network

- The water network provides cold, drinkable tap water.
- Dedicated 1/4" or 3/8" diameter water line.
- Easily accessible dedicated shutoff valve on machine's end.

IMPORTANT – Do NOT use distilled water

