KREA TOUCH

INSTALLATION SITE PREPARATION CHECKLIST

Necta

GENERAL MACHINE ENVIRONMENT

- ☐ The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- ☐ The counter accommodates the machine size and weight:
  - Dimensions: 16.3” (W) x 33.5” (H) x 22.3” (D)
  - Dry Weight: 90 lb
- ☐ For under counter waste bin installation, a hole has been cut in the counter in accordance with model chute kit template.
- ☐ Machine can safely be installed with minimum clearance:
  - Top: 9.9” – Necessary for filling the machine from the top, but it can also be refilled from the front.
  - Sides: 6” – Opening the door and accessing the lock.
  - Back: 1.75” – Electrical and water connections space.

ELECTRICAL REQUIREMENTS

Krea Touch Specifications	120 V / 60 Hz, 1300 W NEMA 5-15P GFCI Plug

- ☐ Power outlet receptacle is NEMA 5-15R.
- ☐ Dedicated electrical circuit meets the Krea Touch power requirements.
- ☐ No extension cord or power strip on the circuit.



WATER REQUIREMENTS

Pressure & Hardness

- ☐ Pressure is between 7.3 psig and 123.3 psig (0.5 and 8.5 bar).
- ☐ pH range is between 6.5 and 7.5.
- ☐ Hardness (TDH) is between 89 PPM and 142 PPM.

MANDATORY – Machine water line must be equipped with a water filtration system with softness/filtration capabilities and a descaling device.

Water Network

- ☐ The water network provides cold, drinkable tap water.
- ☐ Dedicated 1/4" or 3/8” diameter water line.
- ☐ Easily accessible dedicated shutoff valve on machine’s end.

EVOCA GROUP

Evoca North America
2355, avenue Dalton, Québec (Québec) G1P 3S3, Canada
T: 800-561-6162 - F: 800-463-2739
www.evocagroupna.com

Evoca Group Headquarters
Via Roma, 24, 24030 Valbrembo BG Italy
T: +39 035606111 - F: +39 095606560
www.evocagroup.com