la Giusta
INSTALLATION SITE PREPARATION CHECKLIST

GAGGIA MILANO

Model	TALL Version	
	☐ 2-Group	☐ 3-Group
Dimensions (WxHxD)	29.9" x 21.5" x 25"	38.9" x 21.5" x 25"
Weight	172 lb	207 lb
Power Cord Plug	NEMA 6-30P	NEMA 6-50P
Max Absorbed Power	4000 W	5400 W
Voltage & Frequency	220 V / 60 Hz	

GENERAL MACHINE ENVIRONMENT

- ☐ The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- ☐ The counter accommodates the machine size and weight (refer to model table).
- ☐ An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template.
- ☐ Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.
- ☐ Machine can safely be installed with a minimum clearance of 3" from the back wall, 4" on each side and 12" on top.

ELECTRICAL REQUIREMENTS

- ☐ Power outlet receptacle is: NEMA 6-30R (**2-Group** models) or NEMA 6-50R (**3-Group** models).
- ☐ Dedicated electrical circuit meets La Giusta model power requirements.
- ☐ No extension cord or power strip on the circuit.

2-GROUP MODELS
NEMA 6-30

3-GROUP MODELS
NEMA 6-50



Legend
Ground
Hot/Line

WATER REQUIREMENTS

Pressure & Hardness

- ☐ Pressure is between 21.8 PSI & 116.03 PSI.
- ☐ pH range is between 6.5 and 7.5.
- ☐ Hardness (TDS) is between 89 PPM and 142 PPM.

MANDATORY – **Machine water line must be equipped with a water filtration system with softness/filtration capabilities and a descaling device.**

Water Network

- ☐ The water network provides cold, drinkable tap water.
- ☐ Dedicated 3/8" diameter water line.
- ☐ Shutoff valve with a 3/8" G male pipe fitting on machine's end.

HIGHLY RECOMMENDED – Connection to a floor drain in accordance with local health code.