Model	PRO 1G		
	☐ Pour Over	☐ Direct Connection	
Dimensions (WxHxD)	16.8" x 14.5" x 20.2"		
Weight	55 lb		
Power Cord Plug	NEMA 5-15P		
Max Absorbed Power	1640 W		
Voltage & Frequency	120 V / 60 Hz		

GENERAL MACHINE ENVIRONMENT

☐ The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
☐ The counter accommodates the machine size and weight (check selected model).
An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template
☐ Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.
☐ Machine can safely be installed with minimum clearances of 3" from the back wall, 4" on each side and 12" on top.

ELECTRICAL REQUIREMENTS

The electrical configuration must match the Ruby Pro Site Preparation Checklist's electrical requirements, prior to request the installation of the coffee machine. To do so, we recommend that you consult a qualified professional electrician.

Power outlet receptacle is NEMA 5-15R.

Dedicated electrical circuit meets the selected Ruby model power requirements.

No extension cord or power strip on the circuit.

WATER SPECIFICATIONS

The water configuration must match the Ruby Pro Site Preparation Checklist's water specifications, prior to request the installation of the coffee machine. To do so, we recommend that you consult a water filtration system specialist.

pH range is between 6.5 &	7.5.		
☐ Hardness (TDS) is between	89 PPM	& 142	PPM.

Water Network

Pressure is between 2.9 PSI & 72.5 PSI.

The water network provides cold, drinkable tap water.

Dedicated 3/8" diameter water line.

Shutoff valve with a **3/8" G male pipe fitting** on machine's end.

Machine water line is equipped with softness/filtration system and descaling device.

HIGHLY RECOMMENDED: Connection to a floor drain in accordance with local health code.

Evoca North America



