

General Machine Environment

Г	The installation	area is clean	and clear	of dust and	d tools. It is no	ot located in an	active construction zone.

- The counter accommodates the machine size and weight:
 - Dimensions: 19.5" (W) x 43.0" (H) x 26.5" (D)
 - Dry weight: 138 lb
- For under counter waste bin installation, a hole is cut in the counter in accordance with the Emblem chute kit template.
- Machine can safely be installed with minimum clearance:
 - Top: 6" Filling the machine from the top.
 - Sides: 6" Opening the door and accessing the lock.
 - Back: 1.75" Electrical and water connections space.

Electrical Requirements

The electrical configuration must match the Encore Venti Site Preparation Checklist's electrical requirements, prior to request the installation of the coffee machine. To do so, we recommend that you consult a qualified professional electrician.

Encore Venti Specifications

Model	Electrical Specifications	Plug Specifications	
120 V Model	120 V / 60 HZ, 1440 W	NEMA 5-15P GFCI	
220 V Model	220 V (2 phases of 120V) / 60 HZ, 3060 W	NEMA L14-20P	

- Dedicated electrical circuit meets the Encore Venti power requirements.
- No extension cord or power strip on the circuit.

Water Specifications

The water configuration must match the Encore Venti Site Preparation Checklist's water specifications, prior to request the installation of the coffee machine. To do so, we recommend that you consult a water filtration system specialist.

Pressure & Hardness
Cold tap water pressure is at least 20 psi and
no more than 80 psi.
pH range is between 6 and 8.
General hardness is between 10 and 70 mg/L.
Machine water line is equipped with softness/filtration

Water Network

- ☐ The water network provides cold, drinkable tap water.
- Dedicated 1/4" or 3/8" diameter water line.
- Easily accessible dedicated shutoff valve.

IMPORTANT: Do NOT use distilled water





system and descaling device.