

GENERAL MACHINE ENVIRONMENT

The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
The counter accommodates the machine size and weight:
• Dimensions: 16.2" (W) x 28.4" (H) x 21.5" (D)
 Dimensions with NSF/ANSI 4 legs: 16.2" (W) x 31.3" (H) x 21.5" (D)
• Weight: 130 lb
An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template
Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.
Machine can safely be installed with a minimum clearance of 3 3/16" from the back wall.

ELECTRICAL REQUIREMENTS

The electrical configuration must match the Concetto Evo Site Preparation Checklist's electrical requirements, prior to request the installation of the coffee machine. To do so, we recommend that you consult a qualified professional electrician.

Concetto EVO Specifications	Single-phase, 208 V, 60 Hz, 3250 W 3-prong, male NEMA 6-20P power cord plug	
Power outlet receptacle is NEMA 6-20R.		
Dedicated electrical circuit meets the Concetto Evo power requirements.		
■ No extension cord or power	strip on the circuit	

WATER SPECIFICATIONS

The water configuration must match the Concetto Evo Site Preparation Checklist's water specifications, prior to request the installation of the coffee machine. To do so, we recommend that you consult a water filtration system specialist.

Pressure & Hardness
Pressure is between 44 PSI and 116.03 PSI.
pH ranges between 6.5 and 7.5.
Hardness (TDS) is between 89 PPM and 142 PPM.
Machine water line is equipped with softness/filtration system and descaling device.
Water Network
The water network provides cold, drinkable tap water.
Dedicated 3/8" diameter water line.
Shutoff valve with a 3/8" compression fitting on machine's end.

HIGHLY RECOMMENDED: Connection to a floor drain in accordance with local health code.

Evoca North America



