

CONCETTO EVO

INSTALLATION CHECKLIST

GAGGIA
MILANO

GENERAL MACHINE ENVIRONMENT

- The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- The counter accommodates the machine size and weight:
 - Dimensions: 16.2" (W) x 28.4" (H) x 21.5" (D)
 - Dimensions with NSF/ANSI 4 legs: 16.2" (W) x 31.3" (H) x 21.5" (D)
 - Weight: 130 lb
- An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template.
- Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.
- Machine can safely be installed with a minimum clearance of 3 3/16" from the back wall.

ELECTRICAL REQUIREMENTS

Concetto EVO Specifications	Single-phase, 208 V, 60 Hz, 3250 W 3-prong, male NEMA 6-20P power cord plug
------------------------------------	--

- Power outlet receptacle is NEMA 6-20R.
- Dedicated electrical circuit meets the Concetto Evo power requirements.
- No extension cord or power strip on the circuit.

WATER SPECIFICATIONS

Pressure & Hardness

- Pressure is between 44 PSI and 116.03 PSI.
- pH ranges between 6.5 and 7.5.
- Hardness (TDS) is between 89 PPM and 142 PPM.
- Machine water line is equipped with softness/filtration system and descaling device.

Water Network

- The water network provides cold, drinkable tap water.
- Dedicated 3/8" diameter water line.
- Shutoff valve with a 3/8" compression fitting on machine's end.

HIGHLY RECOMMENDED: Connection to a floor drain in accordance with local health code.