# G150 **INSTALLATION CHECKLIST**



### GENERAL MACHINE ENVIRONMENT

	The installation	n area is clean	and clear of	f dust and tools.	It is not located in a	n active construction zone.
--	------------------	-----------------	--------------	-------------------	------------------------	-----------------------------

☐ The counter accommodates the machine size and weight:

- Dimensions: 14.5" (W) x 31" (H) x 23.1" (D)
- Dimensions with NSF/ANSI 4 legs: 14.5 (W) x 33.6 (H) x 23.1 in (D)

An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template

☐ Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.

Machine can safely be installed with a minimum clearance of 1 5/8 inch from the back wall.

### **ELECTRICAL REQUIREMENTS**


120/240 V. 60 Hz. 3690 W **G150 Specifications** NEMA L14-30 Plug

Power outlet receptacle is NEMA L14-30R.

Dedicated electrical circuit meets the G150 power requirements.

No extension cord or power strip on the circuit.





## WATER SPECIFICATIONS

#### Pressure & Hardness

Pressure is between 21.7 PSI and 123.28 PSI.

pH range is between 6.5 and 7.5.

Hardness (TDS) is between 89 PPM and 142 PPM.

Water Network

The water network provides cold, drinkable tap water.

Dedicated 3/8" diameter water line.

Shutoff valve with a 3/8" compression fitting on machine's end.

Machine water line is equipped with softness/filtration system and descaling device.

**HIGHLY RECOMMENDED:** Connection to a floor drain in accordance with local health code.

