

<b>Model</b>	<b>PRO 1G</b>	
	<input type="checkbox"/> Pour Over	<input type="checkbox"/> Direct Connection
<b>Dimensions (WxHxD)</b>	16.8" x 14.5" x 20.2"	
<b>Weight</b>	55 lb	
<b>Power Cord Plug</b>	NEMA 5-15P	
<b>Max Absorbed Power</b>	1640 W	
<b>Voltage &amp; Frequency</b>	120 V / 60 Hz	

## GENERAL MACHINE ENVIRONMENT

- The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- The counter accommodates the machine size and weight (check selected model).
- An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template.
- Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.
- Machine can safely be installed with minimum clearances of 3" from the back wall, 4" on each side and 12" on top.

## ELECTRICAL REQUIREMENTS

- Power outlet receptacle is NEMA 5-15R.
- Dedicated electrical circuit meets the selected Ruby model power requirements.
- No extension cord or power strip on the circuit.

## WATER SPECIFICATIONS

- pH range is between 6.5 & 7.5.
- Hardness (TDS) is between 89 PPM & 142 PPM.

### Water Network

- Pressure is between 2.9 PSI & 72.5 PSI.
- The water network provides cold, drinkable tap water.
- Dedicated 3/8" diameter water line.
- Shutoff valve with a **3/8" G male pipe fitting** on machine's end.
- Machine water line is equipped with softness/filtration system and descaling device.

**HIGHLY RECOMMENDED:** Connection to a floor drain in accordance with local health code.