

# Vetro

## INSTALLATION CHECKLIST

**GAGGIA**  
MILANO

| Model               | STANDARD Version                  |                                   | TALL Version                      |                                   |
|---------------------|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
|                     | <input type="checkbox"/> 2 Groups | <input type="checkbox"/> 3 Groups | <input type="checkbox"/> 2 Groups | <input type="checkbox"/> 3 Groups |
| Dimensions (WxHxD)  | 28.7" x 18.5" x 20.9"             | 35.4" x 18.5" x 20.9"             | 28.7" x 20.5" x 20.9"             | 35.4" x 20.5" x 20.9"             |
| Weight              | 100 lb                            | 137 lb                            | 100 lb                            | 137 lb                            |
| Power Cord Plug     | NEMA 6-20P                        | NEMA 6-30P                        | NEMA 6-20P                        | NEMA 6-30P                        |
| Max Absorbed Power  | 3700 W                            | 4800 W                            | 3700 W                            | 4800 W                            |
| Voltage & Frequency | 220 V / 60 Hz                     |                                   |                                   |                                   |

### GENERAL MACHINE ENVIRONMENT

- The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
- The counter accommodates the machine size and weight (check selected model).
- An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template.
- Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.
- Machine can safely be installed with minimum clearances of 3" from the back wall, 4" on each side and 12" on top.

### ELECTRICAL REQUIREMENTS

- Power outlet receptacle is NEMA 6-20R (2 groups models) or NEMA 6-30R (3 groups models).
- Dedicated electrical circuit meets the selected Vetro model power requirements.
- No extension cord or power strip on the circuit.

### WATER SPECIFICATIONS

#### Pressure & Hardness

- Pressure is between 44 PSI & 116.03 PSI.
- pH range is between 6.5 & 7.5.
- Hardness (TDS) is between 89 PPM & 142 PPM.
- Machine water line is equipped with softness/filtration system and descaling device.

#### Water Network

- The water network provides cold, drinkable tap water.
- Dedicated 3/8" diameter water line.
- Shutoff valve with a **3/8" G male pipe fitting** on machine's end.

**HIGHLY RECOMMENDED:** Connection to a floor drain in accordance with local health code.