

GENERAL MACHINE ENVIRONMENT

The installation area is clean and clear of dust and tools. It is not located in an active construction zor	The instal	allation area is cled	an and clear of dust c	nd tools. It is not loc	cated in an active construction zone.
---	------------	-----------------------	------------------------	-------------------------	---------------------------------------

- \square The machine is installed in a dry room, far from any source of heat (temperature between 41 °F and 93 °F).
- The intallation area accommodates the machine size:
 - Dimensions: 23.6" (W) x 74.0" (H) x 29.1" (D)
- The inclination does not exceed 2 degrees (machine leveled using the adjustable feet, if necessary).
- Machine can safely be installed with minimum clearance:
 - Right Side: 23.6" Complete opening of the door.
 - Front: 20" Opening of the door.
 - Back: 1.6" Providing regular ventilation.

ELECTRICAL REQUIREMENTS

The electrical configuration must match the Opera Touch Site Preparation Checklist's electrical requirements, prior to request the installation of the coffee machine. To do so, we recommend that you consult a qualified professional electrician.

Opera Touch Specifications	110 - 120 V / 60 HZ, 1250 W NEMA 5-15P	
Power outlet receptacle is NEMA 5- Dedicated electrical circuit meets the No extension cord or power strip on		

WATER SPECIFICATIONS

The water configuration must match the Opera Touch Site Preparation Checklist's water specifications, prior to request the installation of the coffee machine. To do so, we recommend that you consult a water filtration system specialist.

Pressure & Hardness

		Water	pressure	is	between	7.3	psig	and	123.0	3 p:	sig	
--	--	-------	----------	----	---------	-----	------	-----	-------	------	-----	--

(0.5 and 8.5 bar).

- \square pH range is between 6.5 and 7.5.
- Hardness (TDH) is between 89 PPM and 142 PPM.
- Machine water line is equipped with softness/filtration system and descaling device.

Water Network

- The water network provides cold, drinkable tap water.
- Dedicated 1/4" or 3/8" diameter water line.
- Easily accessible dedicated shutoff valve.



