



# AULIKA EVO

# **GENERAL MACHINE ENVIRONMENT**

The installation area is clean and clear of dust and tools. It is not located in an active construction zone.

The counter accommodates the machine size and weight:

- Dimensions: 13.15" (W) x 22.6" (H) x 17.8" (D)
- Weight: 48.5 lb

Machine can safely be installed with a minimum clearance of 6 inches on all sides.

# **ELECTRICAL REQUIREMENTS**

6 inch	ies
$\rightarrow$	
	6 inches
6 inches	
6 inches	6 inches
	$\searrow$

Aulika EVO Specifications	120 VAC, 60 Hz, 1400 W NEMA L5-15 Plug
---------------------------	-------------------------------------------

Power outlet receptacle is NEMA 5-15R.

Dedicated breaker.

 $\square$  No extension cord or power strip on the

circuit.

# WATER SPECIFICATIONS

pH range is between 6.5 & 7.5.

Hardness (TDS) is between 89 PPM & 142 PPM.

## Water Network Option

Pressure is between 21.8 PSI & 116 PSI.

The water network provides cold, drinkable tap water.

Dedicated 3/8" diameter water line.

Shutoff valve with a 3/8" G male pipe fitting on machine's end.

Machine water line is equipped with softness/filtration system and descaling device.



2355, avenue Dalton, Québec (Québec) G1P 3S3 Canada T: 800-561-6162 F: 800-463-2739 www.cafectionevoca.com

