LA RADIOSA INSTALLATION CHECKLIST

GENERAL MACHINE ENVIRONMENT

The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
The counter accommodates the machine size and weight:

- Dimensions: 14.5" (W) x 31" (H) x 23.1" (D)
- Dimensions with NSF/ANSI 4 legs: 14.5 (W) x 33.6 (H) x 23.1 in (D)
- Weight: 97 lb

An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.

Machine can safely be installed with a minimum clearance of 1 5/8 inch from the back wall.

ELECTRICAL REQUIREMENTS

 La Radiosa Specifications
 208-240 V, 60 HZ NEMA L6-30P

Power outlet receptacle is NEMA L6-30P.

Dedicated electrical circuit meets the La Radiosa power requirements.

□ No extension cord or power strip on the circuit.



WATER SPECIFICATIONS

Pressure & Hardness

- Pressure is between 21.7 PSI and 123.28 PSI.
- pH range is between 6.5 and 7.5.
- Hardness (TDS) is between 89 PPM and 142 PPM.

Water Network

The water network provides cold, drinkable tap water.
 Dedicated 3/8" diameter water line.

Shutoff valve with a 3/8" compression fitting on machine's end.

☐ Machine water line is equipped with softness/filtration system and descaling device. **HIGHLY RECOMMENDED:** Connection to a floor drain in accordance with local health code.



Evoca North America 2355, avenue Dalton, Québec (Québec) G1P 3S3 Canada T: 800-561-6162 F: 800-463-2739 www.evocagroupna.com

