

Model	1 GROUP	2 GROUPS COMPACT
Dimensions (WxHxD)	17.7" x 16.5" x 20.5"	22.5" x 16.5" x 20.9"
Weight	77.2 lb	101.4 lb
Power Cord Plug	NEMA 5-20P	NEMA 5-20P
Max Absorbed Power	1700 W	1700 W
Voltage & Frequency	115 V / 60 Hz	115 V / 60 Hz

GENERAL MACHINE ENVIRONMENT

The installation area is clean and clear of dust and tools. It is not located in an active construction zone.
The counter accommodates the machine size and weight (check selected model).
An access hole has been pre-drilled in the counter for drainage and power in accordance with model installation template.
Hole in counter is fitted with a collar to protect electrical cord, water line & drain tube.
Machine can safely be installed with minimum clearances of 3" from the back wall, 4" on each side and 12" on top.

ELECTRICAL REQUIREMENTS

The electrical configuration must match La Nera Site Preparation Checklist's electrical requirements, prior to request the installation of the coffee machine. To do so, **we recommend that you consult a qualified professional electrician.**

Power outlet receptacle is NEMA 5-20P.	
Dedicated electrical circuit meets the selected La Nera model power requirements.	
No extension cord or power strip on the circuit.	

WATER SPECIFICATIONS

The water configuration must match La Nera Site Preparation Checklist's water specifications, prior to request the installation of the coffee machine. To do so, we recommend that you consult a water filtration system specialist.

☐ pH range is between 6.5 & 7.5. ☐ Hardness (TDS) is between 89 PPM & 142 PPM.
Water Network
Pressure is between 2.9 PSI & 72.5 PSI.
The water network provides cold, drinkable tap water.
Dedicated 3/8" diameter water line.
Shutoff valve with a 3/8" G male pipe fitting on machine's end.
☐ Machine water line is equipped with softness/filtration system and descaling device



